

SPORTS TOPPER

BIGGEST, LITTLE UNIT IN THE MARKET

A medium-capacity, precision-built topdresser

Hydraulically powered

Variable-speed conveyor floor and high speed dispensing brush

Place sand topdressing down in grass plant

Fill aeration holes to a depth of 30%



FEATURES:

- Powered by tractor hydraulics or optional engine drive hydraulic power pack
- "Walking-beam" axle – tires never crush the turf surface
- Treadles turf tires – consistent pressure of only 8-10 p.s.i. on the surface
- Towable with any turf vehicle
- Topdress wet or dry materials – dispense grass clippings, fill sand traps, top up cart paths with aggregate stone

This may be the only top quality, professional topdresser that fits your budget



0 0 6 0 1

www.sportsturfmagic.com

CANADA 1-800-325-4871

USA 1-800-665-2696

41 Kelfield Street, Rexdale, Ontario, Canada M9W 5A3

BANNERMAN SPORTS TOPPER

SPECIFICATIONS

Weight	Empty	550 lbs.	250 Kg
	Maximum	3800 lbs.	1724 Kg
Dimensions	Length	56 inches	142 cm
	Height	50 inches	127 cm
	Width	70 inches	178 cm
Spread	Width	58 inches	147 cm
	Speed	Variable	
Capacity	Cubic yards	1-3/4 cubic yards	1.34 cubic meters
	Cubic feet	47 cubic feet	9242 cubic cm
Ground Pressure	Only 10-12 p.s.i. when fully loaded		
Drive	Hydraulic to brush		
	Hydraulic to conveyor floor		
	Variable speed attained by means of (20) position restrictor valves – achieving variable depth of topdressing 3/32 inches to 2-1/5 inches.		
Tires	Two pairs twin 18-9:50 x 8 turf tires on centre pivot swing axle to ensure safe flotation, stability, and ensures consistent low p.s.i. on turf surface		
Hopper	Galvanized steel, ribbed, light weight Strong ensuring maximum capacity material yet minimizing overall weight		
Conveyor	Adjustable by means of two front bearing block adjusters		
Brush	8" sectional heavy duty poly-fibre brush at the rear of the conveyor ensures even spreading of all types of organic and sand topdressings Height and spread of the brush thrusts material partially into the grass plant and aeration holes thus requiring less labour for "dragging" with brushes, rakes or drag mats		
Tongue	Clevis style or option ball hitch Adjustable in verticle height to match all turf vehicles		

REQUIREMENTS

Tow Vehicle	15 h.p. minimum with hydraulics		
Hydraulics	Minimum flow	2.6 gallons per minute	12 Litres per minute
	Maximum flow	5.5 gallons per minute	21 Litres per minute
	Minimum pressure	900 p.s.i.	
	Maximum pressure	2000 p.s.i.	

OPTIONAL EQUIPMENT

R19002	Engine driven hydraulic pump comes with oil reservoir kit; 12 volt electric valve and controller, lead and tow hitch
---------------	--

BANNERMAN TOPDRESSERS

Our topdressers are capable of spreading: sand, sand peat loam, sand/soil, organic top soil with leaf mould and reclaimed sewage sludge, manures and soil mix, calcined clay for ball diamond and other infield ball diamond mixes, aggregate stone dust, bark chips, and grass clippings.

Our units spread all material to desired depths evenly over 58" width.

Our units can be calibrated to achieve cost control of the materials to be spread prior to dispensing.