

GREENS THATCHER



Model#: BGT-27

Greens Thatcher

THE HOME OF SPORTSTURF MAGIC



00692

www.sportsturfmagic.com

CANADA 1-800-325-4871

USA 1-800-665-2696

41 Kelfield Street, Rexdale, Ontario, Canada M9W 5A3

GREENS THATCHER

SPECIFICATIONS

As you are aware thatching is an extremely important part of any turf management program. This practice can help remedy situations where the excessive accumulation of thick "grass swards" on existing & new varieties of bentgrass is hindering the performance of the greens, especially older golf courses which may or may not have sand-based putting greens. By pruning the thick swards from the base of the grass plant water, oxygen, & nutrients circulate freely and can be absorbed by the grass roots. Accumulation of sand topdressing is kept to a minimum.

Bannerman Greens Thatcher is designed to provide efficient vertical cutting and removal of dead plant material and other debris. Our blades are offset to prevent tracking of the cutting tips, eliminating ridging, which is particularly important on golf and lawn bowling greens where a uniform smooth surface is essential.

Built for the professional Bannerman Greens Thatchers will give top performance and long, trouble-free service. The depth of cut of the self-sharpening spring steel blades is easily adjustable to suit the condition of the turf and the results desired.

SPECIFICATIONS

| | |
|---------------|---|
| Main Frame | 12 gauge steel, welded. |
| Lower Handle | Welded "H" for strength & "Anti-Twist" |
| Upper Handle | 14 gauge tubular "Roll Around" with cellular Sponge comfort grip. |
| Wheels – Rear | Pneumatic with inner tube, heavy duty steel rims, and greaseable 1/2" bearings |
| Bearings | 2 - Two piece "taper lock" bearing on tempered blade shaft. |
| Drive Belt | 3/8" "toothed" heavy duty positive drive edge. |
| Engine | Honda [Model: GC-1605.0 (Q.H.C.) 5.0 horsepower, 4 cycle] |
| Blades | Quantity of 27 - 1/32" thickness, hardened spring |



| | |
|---------------------------|--|
| Blade Depth | Dual Quick Adjust calibrated control rods - 1/32" increments |
| Operating Weight 122 lbs. | Shipping Weight 127 lbs. |