

COMMERCIAL LINE TRIMMER



Precision built from the best components available.

Smooth running

Easy starting

Lightweight and well balanced

THE HOME OF SPORTSTURFMAGIC

BaNNerman

00700

www.sportsturfmagic.com

CANADA 1-800-325-4871

USA 1-800-665-2696


41 Kelfield Street, Rexdale, Ontario, Canada M9W 5A3

COMMERCIAL LINE TRIMMER - SPECIFICATION CHART

MODEL	BW-2015-M
OVERALL WEIGHT - DRY	13 lbs. (5.9Kg)
OVERALL WEIGHT - WET	14.5 lbs. (6.6Kg)
OVERALL LENGTH	72 inches (182.8 cm)
SHIPPING DETAILS: ENGINE	7 lbs. (3.17Kg) 11" X 10" X 9" (27.9cm X 25.4cm X 22.8cm)
SHIPPING DETAILS: SHAFT	10 lbs. (4.5Kg) 67" X 7" X 5" (170cm X 17.8cm X 12.7cm)
POWER	
ENGINE	Mitsubishi
MODEL	TLE 27
TYPE	Air-cooled, 2 stroke single cylinder, gasoline engine
HORSEPOWER	1.7
R.P.M.	6,500 to 7,000
DISPLACEMENT	25.6cm
FUEL	Gasoline
FUEL MIXTURE	Gasoline to Oil: 50:1
FUEL TANK CAPACITY	1.3 Pints (.615L)
CARBURETOR	Diaphragm (operates in all positions)
STARTER	Recoil Starter Assembly
IGNITION	Electronic - Solid State (Transistor type)
AIR FILTER	Sponge Cushion Element
CYLINDER	Aluminum Alloy Chrome Plated
BORE & STROKE	Minimum 32mm X 30mm
COMPRESSION RATIO	6.5-1
THROTTLE	Throttle Lever with Adjustable Tension Spring
UNIT	
SHAFT - TUBE	Long shaft with balanced design for operator comfort and cutting efficiency, 26mm outside diameter, 23mm inside diameter, 3mm wall thickness. Rigid tubular housing to protect against shaft breakage. Supported with 6 self-lubricating high-speed bushings for anti-vibration within the tube.
CUTTING HEAD R.P.M.	5,200 to 5,700
CLUTCH	Automatic centrifugal clutch geared to optimum cutting head speed. Engages at minimum engine R.P.M. of 3,000 to endure proper cooling and longer engine life.
DRIVE SHAFT	Hardened and splined at both the clutch drum and drive gear ends
DIRECTION OF ROTATION	Counterclockwise
HANDLE	Hook type safety handle with anti vibration rubber palm grip
STANDARD FEATURES	
SHOULDER HARNESS	Attached to a swivel clevis for operator comfort
SAFETY GUARD	Adjustable, high impact plastic, clamp to shaft tube
CUTTING HEAD	Manual - pull and twist to release line - made of high impact plastic
CUTTING HEAD CAPACITY	25 feet of line
ENGINE STAND	Replaceable solid wire support to protect the operator, carburetor, muffler and fuel tank



Blade – Brush 4 tooth
For taller grass areas



Blade – Saw 60 tooth
Pruning/cutting small trees or brush



Line Head (N00BW-LH-10)
Edging & Trimming